DATASHEET

aScope 5 Broncho combines the high level of maneuverability and imaging needed in the bronchoscopy suite with the sterility and efficiency of the singleuse concept. The result? Consistently high performance, sterility, and the flexibility required for a complex and demanding workflow.

Single-use like you've never seen it before

With the launch of the 5th generation of aScope Broncho, Ambu takes flexible bronchoscopy to even greater heights.

Building on over a decade of single-use bronchoscopy know-how, aScope 5 Broncho combines the familiar benefits of reusable scopes with the advantages of the single-use solution. It is compatible with the full HD resolution Ambu[®] aBox[™] 2 displaying and processing unit and can easily be connected to external monitors.

aScope 5 Broncho delivers consistently high performance with excellent maneuverability, next-level imaging and a smart, functional design. This level of performance is complemented by the sterility and efficiency of the Ambu single-use solution to give you the quality and flexibility you need for a complex and demanding workflow in the bronchoscopy suite.

Ambu® aScope™ 5 Broncho HD 5.0/2.2



KEY BENEFITS

Eliminate the need for endoscope reprocessing and repairs

Start or expand bronchoscopy services with minimal capital investment

Easily navigate bronchial segments with bending angles of $195^{\circ}/195^{\circ}$ (up/down)

Designed for smooth insertion and positioning of endotherapy instruments

Choose the right endotherapy instrument without fear of damaging an expensive scope

Visualize bronchial tree clearly with an HD system that offers superior image quality

Seamlessly integrate the aBox 2 displaying and processing unit to your documentation systems

Offer your patient a sterile scope and eliminate the risk of cross-contamination



SPECIFICATIONS

Optical system	
Field of view	120°
Direction of view	0° (forward viewing)
Depth of field	3 - 100 mm
Illumination method	LED
Camera sensor module	CMOS
Insertion portion	
Bending section	195° up, 195° down
Insertion cord diameter	5.0 mm (0.20")
Distal tip diameter	5.4 mm (0.21")
Maximum diameter of insertion portion	Max Ø 5.7 mm (0.22")
Minimum endotracheal tube size (inner diameter)	6.0 mm/18 Fr
Working length	600 mm (23.6")
Rotary function	120° left/right
Depth marks	Every 5 cm
Working channel	
Instrument channel width	2.2 mm (0.9")
Minimum instrument channel width*	Min. Ø 2.05 mm (0.08")
Suction connector	
Connecting tube inner diameter	Ø 5.5 - 9.0 mm
Operating environment, storage, and transporta	tion
Temperature - transportation	-10 - 55 °C (14 to 131 °F)
Temperature - operating environment	10 - 40 °C (50 to 104 °F)
Temperature - storage	10 - 25 °C (50 to 77 °F)
Relative humidity - storage	10 - 85 %
Atmospheric pressure - storage	50 - 106 kPa
Sterilization	
Method of sterilization	ETO
Other	
Compatibility	High-frequency endotherapy instruments, argon plasma coagulation (APC) probes, cryobiopsy probes, Nd-YAG laser probes
Latex and phthalate free	Yes



aScope 5 Broncho HD 5.0/2.2 works with the full HD resolution Ambu[®] aBox[™] 2 displaying and processing unit and can easily be connected to external monitors.

aScope 5 Broncho HD 5.0/2.2 is compatible with endotherapy instruments designed to fit a working channel diameter of up to 2.2mm.

ORDERING SPECIFICATIONS

Item no. 621001000US

Quantity (Ambu[®] aScope[™] 5 Broncho HD 5.0/2.2) 5/box

*There is no guarantee that accessories selected solely using this minimum instrument channel width will be compatible in combination.

Questions? Contact your Ambu representative at **800-262-8462** or visit **www.ambuusa.com/ascope5**



Ambu, Inc. 6721 Columbia Gateway Drive, Suite 200 Columbia, MD 21046 Tel. 800 262 8462 Fax 800 262 8673 ambuUSA.com