SINGLE-USE EVERY CASE, EVERY DAY

The Ambu® aScope™ 5 Uretero opens up a path to a single-use solution that you can confidently use every day for every case - without worrying about performance becoming compromised.

Designed to access difficult-to-reach areas

- Designed to ease insertion with tapered 7.9Fr tip
- 1:1 torque transmission help control movement precisely
- Excellent bending capabilities, with or without tools inserted
- Single-use means no deterioration of performance

Compatible with most common tools

- Designed to work with 10/12Fr ureteral access sheaths or larger
- Compatible with stone removal devices, lasers, guidewires and biopsy forceps

Clear, sharp imaging makes it easy to detect stone fragments

- A high-resolution endoscopy solution
- Sharp image with reduced noise and glare at the corner(s)
- Enhanced visibility with Ambu's proprietary Advanced Red Contrast (ARC) enhancement



BUILT FOR THE ENDOUROLOGY EXPERIENCE

The aScope 5 Uretero solution offers the flexibility needed to fit your existing OR setup. At the heart of the solution is $Ambu^{\otimes} aBox^{\otimes} 2$, a full HD endoscopy system with a compact design that:

- Includes a light source, processor and recorder in one easy-to-use system
- Can be used independently or easily connected to your existing visualization tower to work with your external monitor.
- Is compatible with PACS servers and Electronic Medical Record (EMR) software, making documentation smooth and efficient.



THE WORLD'S FIRST URETEROSCOPE WITH BIOPLASTIC MATERIAL

For over a decade, Ambu has led the way in innovation for singleuse endoscopy with value-added solutions. We are committed to drive sustainability for single-use endoscopy in the same way.

One tangible example of this is by being the first to introduce bioplastic material in the handles of our single-use endoscopes, including aScope 5 Uretero, which:

- Is made from by-products and waste, such as used cooking oil
- Doesn't compete with food and agriculture production
- Reduces the carbon footprint of the ABS plastics used for the production of our ureteroscope handles by 70%

We consider the use of bioplastics as a significant action in our sustainability journey. Our long-term goal is to achieve full recycling of our single-use endoscopes at scale.



Learn about Ambu's sustainability initiatives, including our innovative use of bioplastics.



SPECIFICATIONS

Insertion Portion	
Bending angle	270° up, 270° down
Minimum diameter of the insertion cord	8.1 Fr
Distal end diameter	7.9 Fr
Working length	680 mm
Minimum instrument channel width	3.6 Fr
Optical System	
Field of view	90°
Depth of field	2-50 mm
Image enhancement	Yes
Illumination method	LED

ORDERING SPECIFICATIONS

Product	Item no.	Quantity
Ambu® aScope™ 5 Uretero, Standard Deflection	604101000	5
Ambu® aScope™ 5 Uretero, Reverse Deflection	605101000	5
Ambu® aBox™ 2	505001000US2	1
Accessories	Item no.	Quantity
Hemostasis Valve*	FLO 30	25

Not available in all countries.



Learn more about Ambu aScope 5 Uretero and why you can use it every day for every procedure



Ambu, Inc. 6721 Columbia Gateway Drive, Suite 200 Columbia, Maryland 21046 Tel. 800 262 8462 Fax 800 262 8673 ambuUSA.com